

OPERATOR EXPERIENCE



SCREEN PERFORMANCE

Improve the user experience with a more responsive screen and boot up time of less than a minute

DIGITAL ADVERTISING

Encourage sales while building brand loyalty with display advertising and interactive promotions throughout the purchase experience

PRODUCT VARIETY

Increase sales and consumer satisfaction with a great product selection

CASHLESS PAYMENT

Capture every sale with a built-in and intuitive cashless solution

REMOTE MANAGEMENT

Manage machines over the air with Simplifi™ CONNECT PLUS for price changes, planograms and nutritional information



MERCHANT 6

Specifications

	Merchant 4	Merchant 6
Height	1830 mm	1830 mm
Depth	810 mm*	810 mm*
Width	895 mm	1180 mm
Weight	247 kg	293 kg
Energy Consumption	100 Wh/h	106 Wh/h
*Doors and vandal panels are easily removable to facilitate access through 750 mm (29.5") openings. All dimensions shown are approximate and are for guidance only.		
Electrical Supply	220/240 VAC 50Hz, 4A	
Payment Protocol	M.D.B. (Standard)	
Listings	CE, UL, FCC	
Options	Lockable cash box	
Temperature Control	Programmable refrigerated temperature range 0°C - 23°C	
Refrigerant	R134a CFC Free	
Chilled Model	Programmable refrigerated temperature range 5°C - 21°C	
Refrigerated model without health control	Above barrier: 9°C - 21°C Below barrier: 1°C - 7°C	
Refrigerated model with health control	Above barrier: 9°C - 21°C Below barrier: 1°C - 5°C	